


C PROGRAMMING MOCK TEST

<http://www.tutorialspoint.com>

Copyright © tutorialspoint.com

This section presents you various set of Mock Tests related to **C Programming Framework**. You can download these sample mock tests at your local machine and solve offline at your convenience. Every mock test is supplied with a mock test key to let you verify the final score and grade yourself.



C PROGRAMMING MOCK TEST I

Q 1 - What is the output of the following code snippet?

```
#include<stdio.h>

main()
{
    int const a = 5;

    a++;
    printf("%d", a);
}
```

- A - 5
- B - 6
- C - Runtime error
- D - Compile error

Q 2 - What is the output of the following code snippet?

```
#include<stdio.h>

main()
{
    const int a = 5;

    a++;
    printf("%d", a);
}
```

- A - 5
- B - 6
- C - Runtime error

D - Compile error

Q 3 - What is the output of the below code snippet?

```
#include<stdio.h>

main()
{
    char s[]="hello", t[]="hello";

    if(s==t){
        printf("equal strings");
    }
}
```

A - Equal strings

B - Unequal strings

C - No output

D - Compilation error

Q 4 - What is the output of the below code snippet?

```
#include<stdio.h>

main()
{
    int a = 5, b = 3, c = 4;

    printf("a = %d, b = %d\n", a, b, c);
}
```

A - a=5, b=3

B - a=5, b=3, c=0

C - a=5, b=3, 0

D - compile error

Q 5 - What is the output of the below code snippet?

```
#include<stdio.h>

main()
{
    int a = 1;
    float b = 1.3;
    double c;

    c = a + b;
    printf("%.2lf", c);
}
```

A - 2.30

B - 2.3

C - Compile error

D - 2.0

Q 6 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    enum { india, is=7, GREAT };
    printf("%d %d", india, GREAT);
}
```

A - 0 1.

B - 0 2

C - 0 8

D - Compile error

Q 7 - What is the output of the following code snippet?

```
#include<stdio.h>

main()
{
    char c = 'A'+255;
    printf("%c", c);
}
```

A - A

B - B

C - Overflow error at runtime

D - Compile error

Q 8 - What is the output of the following code snippet?

```
#include<stdio.h>

main()
{
    short unsigned int i = 0;
    printf("%u\n", i--);
}
```

A - 0

B - Compile error

C - 65535

D - 32767

Q 9 - What is the output of the below code snippet?

```
#include<stdio.h>

main()
{
    unsigned x = 5, y=&x, *p = y+0;
    printf("%u", *p);
}
```

- A - Address of x
- B - Address of y
- C - Address of p
- D - 5

Q 10 - What is your comment on the below C statement?

```
signed int *p=(int*)malloc(sizeof(unsigned int));
```

- A - Improper type casting
- B - Would throw Runtime error
- C - Memory will be allocated but cannot hold an int value in the memory
- D - No issue with statement

Q 11 - What is the output of the following code snippet?

```
#include<stdio.h>

main()
{
    int x = 5;

    if(x==5)
    {
        if(x==5) break;
        printf("Hello");
    }
    printf("Hi");
}
```

- A - Compile error
- B - Hi
- C - HelloHi
- D - Hello

Q 12 - What is the output of the following code snippet?

```
#include<stdio.h>
```

```
main()
{
    int x = 5;

    if(x=5)
    {
        if(x=5) break;
        printf("Hello");
    }
    printf("Hi");
}
```

- A - Compile error
- B - Hi
- C - HelloHi
- D - Compiler warning

Q 13 - What is the output of the following code snippet?

```
#include<stdio.h>

main()
{
    int x = 5;

    if(x=5)
    {
        if(x=5) printf("Hello");
    }
    printf("Hi");
}
```

- A - HelloHi
- B - Hi
- C - Hello
- D - Compiler error

Q 14 - What is the output of the below code snippet?

```
#include<stdio.h>

main()
{
    for(;;)printf("Hello");
}
```

- A - Infinite loop
- B - Prints "Hello" once.
- C - No output
- D - Compile error

Q 15 - What is the output of the below code snippet?

```
#include<stdio.h>

main()
{
    for()printf("Hello");
}
```

- A - Infinite loop
- B - Prints "Hello" once.
- C - No output
- D - Compile error

Q 16 - What is the output of the below code snippet?

```
#include<stdio.h>

main()
{
    for(1;2;3)
        printf("Hello");
}
```

- A - Infinite loop
- B - Prints "Hello" once.
- C - No output
- D - Compile error

Q 17 - int x=~1; What is the value of 'x'?

- A - 1
- B - -1
- C - 2
- D - -2

Q 18 - What is the output of the following program?

```
#include<stdio.h>

void f()
{
    static int i;

    ++i;
    printf("%d", i);
}

main()
{
    f();
    f();
    f();
}
```

- A - 1 1 1
- B - 0 0 0
- C - 3 2 1
- D - 1 2 3

Q 19 - What is the output of the following code snippet?

```
#include<stdio.h>

main()
{
    int *p = 15;
    printf("%d", *p);
}
```

- A - 15
- B - Garbage value
- C - Runtime error
- D - Compiler error

Q 20 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    register int x = 5;

    int *p;
    p=&x;
    x++;
    printf("%d", *p);
}
```

- A - Compile error
- B - 5
- C - 6
- D - Garbage value

Q 21 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int x = 65, *p = &x;

    void *q=p;
    char *r=q;
    printf("%c", *r);
}
```

A - Garbage character.

B - A

C - 65

D - Compile error

Q 22 - What is the output of the following program?

```
#include<stdio.h>

void f()
{
    printf("Hello\n");
}
main()
{
    ;
}
```

A - No output

B - Error, as the function is not called.

C - Error, as the function is defined without its declaration

D -Error, as the main function is left empty

Q 23 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    printf("\");
}
```

A - \

D - Compile error

Q 24 - What is the output of the following program?

```
#include<stdio.h>

{
    int x = 1;
    switch(x)
    {
        default: printf("Hello");
        case 1: printf("hi"); break;
    }
}
```

A - Hello

B - Hi

C - HelloHi

D - Compile error

Q 25 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    struct { int x;} var = {5}, *p = &var;

    printf("%d %d %d", var.x, p->x, (*p).x);
}
```

A - 5 5 5

B - 5 5 garbage value

C - 5 5 0

D - Compile error

Q 26 - What is the output of the following program?

```
#include<stdio.h>

void swap(int m, int n)
{
    int x = m;

    m = n;
    n = x;
}

main()
{
    int x=5, y=3;

    swap(x,y);
    printf("%d %d", x, y);
}
```

A - 3 5

B - 5 3

C - 5 5

D - Compile error

Q 27 - What will be printed for the below statement?

```
#include<stdio.h>

main()
{
    printf("%d", strcmp("strcmp()", "strcmp()));
}
```

A - 0

B - 1

C - -1

D - Invalid use of strcmp function

Q 28 - What is the following program doing?

```
#include<stdio.h>

main()
{
    FILE *stream=fopen("a.txt", 'r');
}
```

A - Trying to open "a.txt" in read mode

B - Trying to open "a.txt" in write mode.

C - "stream" is an invalid identifier

D - Compile error

Q 29 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int r, x = 2;
    float y = 5;

    r = y%x;
    printf("%d", r);
}
```

A - 1

B - 0

C - 2

D - Compile error

Q 30 - Which operator is used to continue the definition of macro in the next line?

A - #

B - ##

C - \$

D - \

Q 31 - What is the size of the following union definition?

```
#include<stdio.h>

union abc {
    char a,b,c,d,e,f,g,h;
    int i;
```

```
}abc;  
  
main()  
{  
    printf( "%d", sizeof( abc ));  
}
```

- A - 1
- B - 2
- C - 4
- D - 8

Q 32 - What is the size of 'int'?

- A - 2
- B - 4
- C - 8
- D - Compiler dependent

Q 33 - The type name/reserved word 'short' is ____

- A - short long
- B - short char
- C - short float
- D - short int

Q 34 - What is the value of 'y' for the following code snippet?

```
#include<stdio.h>  
  
main()  
{  
    int x = 1;  
    float y = x>>2;  
    printf( "%f", y );  
}
```

- A - 4
- B - 0.5
- C - 0
- D - 1

Q 35 - What is the output of the following program?

```
#include<stdio.h>
```

```
main()
{
    float t = 2;

    switch(t)
    {
        case 2: printf("Hi");
        default: printf("Hello");
    }
}
```

- A - Hi
- B - HiHello
- C - Hello
- D - Error

Q 36 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int i = 1;

    while(++i <= 5)
        printf("%d ", i++);
}
```

- A - 1 3 5
- B - 2 4
- C - 2 4 6
- D - 2

Q 37 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int i = 1;

    while( i++<=5 )
        printf("%d ", i++);
}
```

- A - 1 3 5
- B - 2 4
- C - 2 4 6
- D - 2

Q 38 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int i = 1;

    while(i++<=5);
    printf("%d ",i++);
}
```

- A - 4
- B - 6
- C - 2 6
- D - 2 4

Q 39 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int x = 1;

    do
        printf("%d ", x);
    while(x++<=1);
}
```

- A - 1
- B - 1 2
- C - No output
- D - Compile error

Q 40 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int a[] = {1,2}, *p = a;

    printf("%d", p[1]);
}
```

- A - 1
- B - 2
- C - Compile error
- D - Runtime error

Q 41 - What is the output of the following program?

```
#include<stdio.h>
```

```
main()
{
    int a[3] = {2,1};
    printf("%d", a[a[1]]);
}
```

A - 0

B - 1

C - 2

D - 3

Q 42 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int a[3] = {2,,1};
    printf("%d", a[a[0]]);
}
```

A - 0

B - 1

C - 2

D - Compile error

Q 43 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int a[] = {2,1};
    printf("%d", *a);
}
```

A - 0

B - 1

C - 2

D - Compile error.

Q 44 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int i = 1;
```

```
Charminar:
printf("%d ", i++);
if(i==3) break;
if(i<=5) goto Charminar;
}
```

- A - 1 2
- B - 1 2 3
- C - 1 2 4 5
- D - Compile error

Q 45 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    int i = 13, j = 60;

    i ^= j;
    j ^= i;
    i ^= j;

    printf("%d %d", i, j);
}
```

- A - 73 73
- B - 60 13
- C - 13 60
- D - 60 60

Q 46 - What is the output of the following program?

```
#include<stdio.h>

main()
{
    union abc {
        int x;
        char ch;
    }var;

    var.ch = 'A';
    printf("%d", var.x);
}
```

- A - A
- B - Garbage value
- C - 65
- D - 97

Q 47 - Identify the incorrect file opening mode from the following.

- A - r
- B - w
- C - x
- D - a

Q 48 - Function fopen with the mode "r+" tries to open the file for __

- A - reading and writing
- B - reading and adding new content
- C - only for reading
- D - it works only for directories

Q 49 - Identify the invalid constant used in fseek function as 'whence' reference.

- A - SEEK_SET
- B - SEEK_CUR
- C - SEEK_BEG
- D - SEEK_END

Q 50 - First operating system developed using C programming language.

- A - DOS
- B - Windows
- C - UNIX
- D - Mac

ANSWER SHEET

Question Number	Answer Key
-----------------	------------

- | | |
|---|---|
| 1 | D |
| 2 | D |
| 3 | C |
| 4 | A |
| 5 | A |
| 6 | C |
| 7 | A |
| 8 | A |

9	D
10	D
11	A
12	A
13	A
14	A
15	D
16	A
17	D
18	D
19	C
20	A
21	B
22	A
23	D
24	B
25	A
26	B
27	A
28	D
29	D
30	D
31	C
32	D
33	D
34	C
35	D
36	B
37	C
38	B
39	B
40	B
41	B
42	D
43	C

44	D
45	B
46	C
47	C
48	A
49	C
50	C

Loading [MathJax]/jax/output/HTML-CSS/jax.js